

instruction manual


TELESCOPIC CHANNEL RAMP weight cap. 600 lbs. [300 lbs per track]

Caution.

Use ramp ONLY with a qualified helper, NEVER exceed the recommended weight limit during use. Always back the chair down the ramp and use a lap belt for safety. See the owners manual of the chair or scooter being used to determine an acceptable incline.

Using the Ramp.

1. Slide the inner channel out until it meets the stops
2. Space the tracks so that the wheels of the vehicle run on the center of the skid resistant tape. The tracks should be firmly against the landing so that the threshold plate rests securely on the landing.
3. Two pins are supplied to help anchor the ramp into position. When you are satisfied that the ramp is positioned properly, drill a 1/4" hole 1 1/2" deep into the landing or vehicle floor using the prepunched holes in the top adapter lip as a guide. Complete the installation by inserting the anchor pins through the threshold plate and into the drilled holes.



Maintenance & Safety

1. Regularly check your ramp for worn, loose, or damaged parts. If you find any of these conditions DO NOT USE THE RAMP. Contact your Dealer for repairs. Failure to do so may cause severe injury !
2. The surface of the ramp may become slippery in icy or wet conditions. Caution should be used when using the ramp.
3. Keep the ramp surface free of dirt and debris.
4. Always check the chair or scooter for the manufacturer's recommended degree of incline. Do not use ramps that are steeper than recommended.
5. Do not add to or modify any part of the ramp. Doing so may void your warranty.
6. Do not use the ramp for purposes other than those it was designed for.
7. Clean ramps with water and mild detergent.
8. Use caution when folding and unfolding your ramp. Beware of pinch points.
9. Be sure that the ramp is always on a solid landing and firmly placed. Always anchor your ramp in place with the pins provided.

bridging the gap.

ALUMIRAMP, Inc. 855 Chicago Road, Quincy, MI 49082 tel 800.800.3864 fax 800.753.7267